

**Pressure sensitive electric switch**Patent Number:  [GB2064873](#)

Publication date: 1981-06-17

Inventor(s):

Applicant(s): EVENTOFF FRANKLIN NEAL

Requested  
Patent: [SE8008205](#) ←Application  
Number:

GB19800037047 19801119

Priority Number (s): US19790097610 19791126; US19800110416 19800107; US19800135386 19800331; US19800140921 19800416; US19800140937 19800416


IPC

Classification: H01H1/02; H01H13/52

EC Classification: [B60C23/04C](#), [H01H1/02B](#), [H01H13/70B](#)

Equivalents:

AU544234, CA1153801,  [DE3044384](#),  [FR2470435](#),  [GB2134320](#),  [GB2134321](#),  
 [GB2134322](#),  [IT1143185](#),  [NL8006409](#),  [SE452925](#)**Abstract**

A pressure responsive electric switch has at least one pair of first (104) and second (112) conductors in spaced- apart relationship with at least one pressure sensitive resistive conductor (106, 114) is disposed in a position to interconnect the conductors when a force is applied. The invention may be incorporated in multiple touch switches having the conductors (220, 240) Figure 7 disposed side by side or stacked one above the other as in Figure 10 (not shown). The resistive conductor may be made from molybdenum disulphide particles with a resin binder and may include powdered carbon. 

Data supplied from the esp@cenet database - I2